

GAS FOR LIVESTOCK FARMING

XLA AUTOMATIC LIFTING

Natural gas or propane – supply pressure from 60 to 148 mbar



Technical Specifications

	208 XLA	212 XLA	216 XLA
Maximum power Hs (kW) (p = 148 mbar)	7,2	10,8	14,1
Maximum Power (Hi) (kW) (p = 148 mbar)	6,6	10,0	13,0
Minimum power Hs (kW) (p = 60 mbar)	3,6	5,4	7,0
Minimum Hi Power (kW) (p = 60 mbar)	3,2	4,9	6,3
Gas consumption at p = 148 mbar (g/h)	520	780	1 020
Gas consumption at p = 60 mbar (g/h)	260	390	510
Injector Size	2 x 65	2 x 78	2 x 95
Maximum combustion air (m ³ /h)	6,6	10,0	13,0

Benefits of the SBM XLA Series Brooder Chickens

- ✓ Fully automatic feeder : 50%, 100%, STOP
- ✓ Heating area up to 160 m²
- ✓ A single heating line for buildings less than 16 m wide
- ✓ Ceramic infrared emitter = optimal efficiency
- ✓ Equipped with a stainless steel mesh filter
- ✓ Compatible with any livestock management computer thanks to SUNMASTER SAT
- ✓ Easy to install, use, and maintain

Installation with 216 XLAs

